



# 3/4" DRIVE IMPACT SOCKETS



## 12 PT. DEEP IMPACT SOCKETS

12

| PART NUMBER | NOM. SIZE | RET RING | SHAPE | L      | DS      | DD       | BD     |
|-------------|-----------|----------|-------|--------|---------|----------|--------|
| 6969        | 9/16"     | 6581     | I     | 3-1/4" | 1"      | 1-5/8"   | 21/64" |
| 6970        | 5/8"      | 6581     | I     | 3-1/4" | 1-3/32" | 1-5/8"   | 3/8"   |
| 6972        | 11/16"    | 6581     | I     | 3-1/4" | 1-5/32" | 1-5/8"   | 3/8"   |
| 6974        | 3/4"      | 6581     | I     | 3-1/4" | 1-1/4"  | 1-5/8"   | 7/16"  |
| 6976        | 13/16"    | 6581     | I     | 3-1/4" | 1-3/8"  | 1-5/8"   | 29/64" |
| 6978        | 7/8"      | 6581     | I     | 3-1/4" | 1-1/2"  | 1-5/8"   | 1/2"   |
| 6980        | 15/16"    | 6581     | I     | 3-1/4" | 1-9/16" | 1-5/8"   | 35/64" |
| 6982        | 1"        | 6581     | II    | 3-1/4" | 1-5/8"  | 1-5/8"   | 35/64" |
| 6998        | 1-1/2"    | 6581     | III   | 3-1/2" | 2-5/16" | 1-29/32" | 7/8"   |

Meets or exceeds ASME B107.110.




## 6 PT. DEEP METRIC IMPACT SOCKETS

6


| PART NUMBER | NOM. SIZE | RET RING | SHAPE | L     | DS    | DD    | BD    |
|-------------|-----------|----------|-------|-------|-------|-------|-------|
| 69-19mm     | 19mm      | 6581     | I     | 78.97 | 31.75 | 41.28 | 11.13 |
| 69-21mm     | 21mm      | 6581     | I     | 78.97 | 34.93 | 41.28 | 11.51 |
| 69-22mm     | 22mm      | 6581     | I     | 78.97 | 34.93 | 41.28 | 12.70 |
| 69-23mm     | 23mm      | 6581     | I     | 78.97 | 38.89 | 41.28 | 12.70 |
| 69-24mm     | 24mm      | 6581     | I     | 78.97 | 39.70 | 41.28 | 14.30 |
| 69-26mm     | 26mm      | 6582     | I     | 88.90 | 41.28 | 44.45 | 63.42 |
| 69-27mm     | 27mm      | 6582     | I     | 88.90 | 42.88 | 44.45 | 63.10 |
| 69-30mm     | 30mm      | 6582A    | II    | 88.90 | 47.75 | 47.75 | 62.09 |
| 69-31mm     | 31mm      | 6582A    | II    | 88.90 | 45.72 | 45.72 | 60.00 |
| 69-32mm     | 32mm      | 6582A    | II    | 88.90 | 50.80 | 50.80 | 61.42 |
| 69-33mm     | 33mm      | 6582A    | II    | 88.90 | 50.80 | 50.80 | 61.09 |
| 69-34mm     | 34mm      | 6582A    | II    | 88.90 | 52.58 | 52.58 | 60.00 |
| 69-35mm     | 35mm      | 6582A    | III   | 88.90 | 53.98 | 48.26 | 61.12 |
| 69-36mm     | 36mm      | 6582A    | III   | 88.90 | 53.98 | 48.26 | 60.67 |
| 69-38mm     | 38mm      | 6582A    | III   | 88.90 | 58.75 | 48.26 | 60.01 |
| 69-41mm     | 41mm      | 6582A    | III   | 88.90 | 61.93 | 48.26 | 59.01 |
| 69-43mm     | 43mm      | 6582A    | III   | 88.90 | 63.50 | 48.26 | 58.34 |
| 69-46mm     | 46mm      | 6582A    | III   | 88.90 | 68.58 | 48.26 | 60.00 |
| 69-50mm     | 50mm      | 6582A    | III   | 95.25 | 73.41 | 48.26 | 60.00 |

Meets or exceeds ASME B107.110.


### REFERENCE DIAGRAMS



SHAPE I



SHAPE II



SHAPE III



**WARNING: WEAR  
SAFETY GOGGLES USER  
AND BYSTANDER**



**WARNING: TOOL  
SAFETY INFO READ  
PAGES 376-379**



**WARNING: COMFORT OR  
PLASTIC GRIPS DO NOT PROTECT  
AGAINST ELECTRIC SHOCK**



**WARNING: ALWAYS USE A  
RET RING® WHEN WORKING  
WITH IMPACT PRODUCTS**

**WRIGHT**