



TORQUE SCREWDRIVERS



TORQUE SCREWDRIVERS—MICRO ADJUSTABLE

Precision instrument for precise tightening on installation applications. Accurate, $\pm 6\%$ clockwise direction only @ 20% to 100% of scale range. Pull out adjusting knob to unlock, turn the knob for desired setting, push knob in until it clicks. Cam-over torque limiting clutch. 1/4" internal Hex x 3/8" deep Bit Holder with strong, rare earth magnet to secure bit. Triobular comfort grip. Each torque screwdriver has its own serial number and plastic storage box. Certificate of Calibration traceable to N.I.S.T. Meets or exceeds ASME B107.300 Torque Instrument standard.

PART NUMBER	DRIVE SIZE (INCH)	ACCURATE TORQUE RANGE ENGLISH	UOM	INCR	HEAD STYLE (INCH)	LENGTH (INCH)	HOLDER DIAMETER (INCH)	GRIP OD (INCH)	PART WEIGHT (LBS)	SHIP WEIGHT (LBS)
2462	1/4	20-100	in-oz	1.00	1/4 Hex Holder	5-1/2	0.43	1.10	0.43	0.55
2463	1/4	3-15	in-lbs	0.20	1/4 Hex Holder	6-1/4	0.43	1.10	0.50	0.61
2464	1/4	8-40	in-lbs	0.50	1/4 Hex Holder	6-3/4	0.43	1.20	0.67	0.78

Note: See page 141-143 1/4" shank replacement bits and part numbers.



AUTOMATIC LOCK IN COUNTER-CLOCKWISE DIRECTION MAKES SCREW REMOVAL A SNAP

EASY TO READ WINDOW SCALE

PERMANENTLY LUBRICATED INTERNAL MECHANISM NEVER NEEDS OIL

POSITIVE LOCKING PULL DOWN ADJUSTMENT KNOB

IMPORTANT INFORMATION

TORQUE WRENCH RECALIBRATION

If the user does not utilize a control procedure, the lesser of 12 months usage or 5000 cycles shall be used as the default for the recalibration interval. For the first calibration, the period of validity starts with the user's first operation of the tool. Torque wrenches shall be recalibrated immediately if they are dropped or damaged. Clean torque wrenches after use and store properly at their lowest setting.

TORQUE WRENCH WARRANTY

All Wright Tool torque wrenches are warranted against defects in materials or workmanship for a period of one year from the date of purchase. One of our authorized repair facilities, at their discretion, will repair or replace any defective Wright torque wrench returned to their place of business, postage or freight prepaid. All torque wrenches must be accompanied with a dated copy of the sales receipt or purchase order.

The foregoing obligation is Wright Tool's sole liability and the purchaser's sole remedy under this warranty. There are no other warranties expressed or implied, including those of market ability or fitness for purpose. Under no

circumstances shall Wright Tool be liable for any special, incidental or consequential damages. This warranty does not apply if the torque wrench has been altered, damaged, abused or improperly maintained. This warranty gives you specific legal rights and you may have other rights which vary from state to state.

Note: Please contact Wright Tool Customer Service at 1-800-321-2902 or FAX 1-800-543-2095 for shipping instructions on the return of all torque wrenches for warranty, repairs or other services. All warranty considerations will be returned to the customer freight prepaid. All non-warranty repairs or calibrations will be returned to the customer with all applicable charges and freight collect.



WARNING: WEAR SAFETY GOGGLES USER AND BYSTANDER



WARNING: TOOL SAFETY INFO READ PAGES 376-379



WARNING: COMFORT OR PLASTIC GRIPS DO NOT PROTECT AGAINST ELECTRIC SHOCK

